

ABC CABLE SERVICE DROP

DUPLEX SERVICE DROP CABLE

Code Word	AWG or kcmil	Bare Neutral Messenger		Phase Conductor		Weight (kg/km)
		AAC Stranding and Wires Dia. (mm)	Rated Strength (lbs)	AAC Stranding and Wires Dia. (mm)	Insul. Thick. (mm)	
Pekingese	1*6AWG+1*6AWG	7/1.56	563	1/4.11	1.14	92
Collie	1*6AWG+1*6AWG	7/1.56	563	7/1.56	1.14	94
Dachshund	1*4AWG+1*4AWG	7/1.96	881	1/5.19	1.14	139
Spaniel	1*4AWG+1*4AWG	7/1.96	881	7/1.96	1.14	141
Doberman	1*4AWG+1*2AWG	7/2.47	1350	7/2.47	1.14	216
Malemute	1*1/0AWG+1*1/0AWG	7/3.12	1990	19/1.89	1.52	347

Code Word	AWG or kcmil	Bare Neutral Messenger		Phase Conductor		Weight (kg/km)
		ACSR Stranding and Wires Dia. (mm)	Rated Strength (lbs)	AAC Stranding and Wires Dia. (mm)	Insul. Thick. (mm)	
Setter	1*6AWG+1*6AWG	1/1.68+6/1.68	1190	1/4.11	1.14	111
Shepherd	1*6AWG+1*6AWG	1/1.68+6/1.68	1190	7/1.56	1.14	113
Eskimo	1*4AWG+1*4AWG	1/2.12+6/2.12	1860	1/5.19	1.14	171
Terrier	1*4AWG+1*4AWG	1/2.12+6/2.12	1860	7/1.96	1.14	173
Chow	1*2AWG+1*2AWG	1/2.67+6/2.67	2850	7/2.47	1.14	266
Bull	1*1/0AWG+1*1/0AWG	1/3.37+6/3.37	4380	19/1.89	1.52	427

Code word	AWG or kcmil	Bare Neutral Messenger		Phase Conductor		Weight (kg/km)
		AAC Stranding and Wires Dia. (mm)	Rated Strength (lbs)	AAC Stranding and Wires Dia. (mm)	Insul. Thick. (mm)	
Chihuahua	1*6AWG+1*30.58	7/1.68	1110	1/4.11	1.14	98
Vizsla	1*6AWG+1*30.58	7/1.68	1110	7/1.56	1.14	100
Harrier	1*4AWG+1*48.69	7/2.12	1760	1/5.19	1.14	149
Whippet	1*4AWG+1*48.69	7/2.12	1760	7/1.96	1.14	151
Schnauzer	1*2AWG+1*77.47	7/2.47	2800	7/2.47	1.14	231
Heeler	1*1/0AWG+1*123.3	7/3.37	4460	19/1.89	1.52	372

TRIPLEX SERVICE DROP CABLE

Code Word	AWG or kcmil	Bare Neutral Messenger		Phase Conductor		Weight (kg/km)
		AAC Stranding and Wires Dia. (mm)	Rated Strength (lbs)	AAC Stranding and Wires Dia. (mm)	Insul. Thick. (mm)	
Haiotis	2*6AWG+1*6AWG	7/1.56	563	1/4.11	1.14	146
Patella	2*6AWG+1*6AWG	7/1.56	563	7/1.56	1.14	150
Fusus	2*4AWG+1*4AWG	7/1.96	881	1/5.19	1.14	219
Oyster	2*4AWG+1*4AWG	7/1.96	881	7/1.96	1.14	224
Clam	2*2AWG+1*2AWG	7/2.47	1350	7/2.47	1.14	338
Murex	2*1/0AWG+1*1/0AWG	7/3.12	1990	7/3.12	1.52	544

Code Word	AWG or kcmil	Bare Neutral Messenger		Phase Conductor		Weight (kg/km)
		AL-ALLOY Stranding and Wires Dia. (mm)	Rated Strength (lbs)	AAC Stranding and Wires Dia. (mm)	Insul. Thick. (mm)	
Minex	2*6AWG+1*30.58	7/1.68	1110	1/4.11	1.14	152
Hippa	2*6AWG+1*30.58	7/1.68	1110	7/1.56	1.14	156
Prawn	2*4AWG+1*48.69	7/2.12	1760	1/5.19	1.14	229
Bamacle	2*4AWG+1*48.69	7/2.12	1760	7/1.96	1.14	233
Shrimp	2*2AWG+1*77.47	7/2.67	2800	7/2.47	1.14	354
Cammarus	2*1/0AWG+1*123.3	7/3.37	4460	7/3.12	1.52	569

Code Word	AWG or kcmil	Bare Neutral Messenger			Phase Conductor		Weight (kg/km)
		ACSR Stranding and Wires Dia. (mm)		Rated Strength (lbs)	AAC Stranding and Wires Dia. (mm)	Insul. Thick. (mm)	
		ST	AL				
Paludian	2*6AWG+1*6AWG	1/1.68	6/1.68	1190	1/4.11	1.14	166
Voluta	2*6AWG+1*6AWG	1/1.68	6/1.68	1190	7/1.56	1.14	170
Whelk	2*4AWG+1*4AWG	1/2.12	6/2.12	1860	1/5.19	1.14	251
Periwinkle	2*4AWG+1*4AWG	1/2.12	6/2.12	1860	7/1.96	1.14	255
Conch	2*2AWG+1*2AWG	1/2.67	6/2.67	2850	7/2.47	1.14	389
Neritina	2*1/0AWG+1*1/0AWG	1/3.37	6/3.37	4380	7/3.12	1.52	624